



DESCRIPTIVE

- Mechanic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for core temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts (CE option)
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPa (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

K17M

| | |
|-------------------|----------|
| Engine ref. | KD11903M |
| Alternator ref. | KH00630T |
| Performance class | G2 |

GENERAL CHARACTERISTICS

| | |
|------------------------|------------------|
| Frequency (Hz) | 50 Hz |
| Voltage (V) | 230 single phase |
| Standard Control Panel | APM303 |
| Optional control panel | TELYS |
| Optional Control Panel | M80 |
| Optional control panel | APM403 |

POWER

| Voltage | ESP | | PRP | | Standby Amps |
|----------|------|------|------|------|--------------|
| | kWe | kVA | kWe | kVA | |
| 240 MONO | 15,5 | 15,5 | 14,1 | 14,1 | 65 |
| 230 MONO | 15,5 | 15,5 | 14,1 | 14,1 | 67 |
| 220 MONO | 15,5 | 15,5 | 14,1 | 14,1 | 70 |

DIMENSIONS COMPACT VERSION

| | |
|-------------------|------|
| Length (mm) | 1410 |
| Width (mm) | 720 |
| Height (mm) | 1080 |
| Dry weight (kg) | 530 |
| Tank capacity (L) | 50 |

DIMENSIONS SOUNDPROOFED VERSION

| | |
|--------------------------------------|------|
| Type soundproofing | M126 |
| Length (mm) | 1750 |
| Width (mm) | 775 |
| Height (mm) | 1230 |
| Dry weight (kg) | 700 |
| Tank capacity (L) | 50 |
| Acoustic pressure level @1m in dB(A) | 71 |
| Sound power level guaranteed (Lwa) | 87 |
| Acoustic pressure level @7m in dB(A) | 58 |



K17M

ENGINE CHARACTERISTICS

GENERAL ENGINE DATA

| | |
|---|---------------|
| Engine brand | KOHLER DIESEL |
| Engine ref. | KDI1903M |
| Air inlet system | Athmo |
| Cylinders configuration | L |
| Number of cylinders | 3 |
| Displacement (L) | 1,86 |
| Charge Air coolant | |
| Bore (mm) x Stroke (mm) | 88 x 102 |
| Compression ratio | 18.5 : 1 |
| Speed (RPM) | 1500 |
| Pistons speed (m/s) | 5,10 |
| Maximum stand-by power at rated RPM (kW) | 19 |
| Frequency regulation, steady state (%) +/- 2.5% | |
| BMEP @ PRP 50 Hz (bar) | 7,40 |
| Governor type | Mechanical |

COOLING SYSTEM

| | |
|--|-----------------|
| Radiator & Engine capacity (L) | 6,80 |
| Fan power (kW) | 0,50 |
| Fan air flow w/o restriction (m3/s) | 0,65 |
| Available restriction on air flow (mm H2O) | |
| Type of coolant | Glycol-Ethylene |

EMISSIONS

| | |
|-------------------------|------|
| Emission PM (g/kW.h) | 0,20 |
| Emission CO (g/kW.h) | 2,38 |
| Emission HC+NOx (g/kWh) | 0 |
| Emission HC (g/kW.h) | |

EXHAUST

| | |
|---|-----|
| Exhaust gas temperature @ ESP 50Hz (°C) | 520 |
| Exhaust gas flow @ ESP 50Hz (L/s) | 59 |
| Max. exhaust back pressure (mm H2O) | 500 |

FUEL

| | |
|-----------------------------------|------|
| Consumption @ 100% load ESP (L/h) | 5 |
| Consumption @ 100% PRP load (L/h) | 4,50 |
| Consumption @ 75% PRP load (L/h) | 3,30 |
| Consumption @ 50% PRP load (L/h) | 2,30 |
| Maximum fuel pump flow (L/h) | 30 |

OIL

| | |
|---|------|
| Oil system capacity including filters (L) | 8,70 |
| Min. oil pressure (bar) | 1,50 |
| Max. oil pressure (bar) | 10 |
| Oil consumption 100% ESP 50Hz (L/h) | 0,01 |
| Oil sump capacity (L) | 8,50 |

HEAT BALANCE

| | |
|-----------------------------------|----|
| Heat rejection to exhaust (kW) | 13 |
| Radiated heat to ambient (kW) | 4 |
| Heat rejection to coolant HT (kW) | 17 |

AIR INTAKE

| | |
|----------------------------------|-------|
| Max. intake restriction (mm H2O) | 150 |
| Intake air flow (L/s) | 18,70 |

GENERAL DATA

| | |
|---|----------------|
| Alternator ref. | KH00630T |
| Number of Phase | Single phase |
| Power factor (Cos Phi) | 1 |
| Altitude (m) | 0 à 1000 |
| Overspeed (rpm) | 2250 |
| Number of pole | 4 |
| Capacity for maintaining short circuit at 3 In for 10 s | Yes |
| Insulation class | H |
| T° class (H/125°), continuous 40°C | H / 125°K |
| T° class (H/163°C), standby 27°C | H / 163°K |
| Total Harmonic Distortion in no-load DHT (%) | 3,3 |
| AVR Regulation | Yes |
| Total Harmonic Distortion, on linear load DHT (%) | 2,1 |
| Wave form : NEMA=TIF | <45 |
| Wave form : CEI=FHT | <2 |
| Number of bearing | Single Bearing |
| Coupling | Direct |
| Voltage regulation at established rating (+/- %) | 1 |
| Recovery time (Delta U = 20% transient) (ms) | 200 |
| Indication of protection | IP 23 |
| Technology | Brushless |

OTHER DATA

| | |
|---|--------|
| Continuous Nominal Rating 40°C (kVA) | 20,50 |
| Standby Rating 27°C (kVA) | 22,20 |
| Efficiencies 100% of load (%) | 82,60 |
| Air flow (m3/s) | 0,0880 |
| Short circuit ratio (Kcc) | 0,68 |
| Direct axis synchro reactance unsaturated (Xd) (%) | 173,40 |
| Quadra axis synchro reactance unsaturated (Xq) (%) | 74,80 |
| Open circuit time constant (T'do) (ms) | 930 |
| Direct axis transient reactance saturated (X'd) (%) | 18,50 |
| Short circuit transient time constant (T'd) (ms) | 46 |
| Direct axis subtransient reactance saturated (X''d) (%) | 10,60 |
| Subtransient time constant (T''d) (ms) | 12 |
| Quadra axis subtransient reactance saturated (X''q) (%) | 22,80 |
| Subtransient time constant (T''q) (ms) | 12 |
| Zero sequence reactance unsaturated (Xo) (%) | 3,04 |
| Negative sequence reactance saturated (X2) (%) | 15,80 |
| Armature time constant (Ta) (ms) | 11 |
| No load excitation current (io) (A) | 0,60 |
| Full load excitation current (ic) (A) | 2,80 |
| Full load excitation voltage (uc) (V) | 30,10 |
| Engine start (Delta U = 20% perm. or 30% trans.) (kVA) | 63,10 |
| Transient dip (4/4 load) - PF : 0,8 AR (%) | 12,90 |
| No load losses (W) | 785 |
| Heat rejection (W) | 4318 |
| Unbalanced load acceptance ratio (%) | 100 |

DIMENSIONS

Dimensions soundproofed version

| | |
|--------------------------------------|------|
| Type soundproofing | M126 |
| Length (mm) | 1750 |
| Width (mm) | 775 |
| Height (mm) | 1230 |
| Dry weight (kg) | 700 |
| Tank capacity (L) | 50 |
| Acoustic pressure level @1m in dB(A) | 71 |
| Sound power level guaranteed (Lwa) | 87 |
| Acoustic pressure level @7m in dB(A) | 58 |

Dimensions DW compact version

| | |
|--------------------------------------|------|
| Type soundproofing | |
| Length (mm) | 1797 |
| Width (mm) | 775 |
| Height (mm) | 1240 |
| Dry weight (kg) | 680 |
| Tank capacity (L) | 93 |
| Acoustic pressure level @1m in dB(A) | |
| Sound power level guaranteed (Lwa) | |
| Acoustic pressure level @7m in dB(A) | |

Dimensions DW soundproofed version

| | |
|--------------------------------------|---------|
| Type soundproofing | M126 DW |
| Length (mm) | 1797 |
| Width (mm) | 775 |
| Height (mm) | 1391 |
| Dry weight (kg) | 850 |
| Tank capacity (L) | 93 |
| Acoustic pressure level @1m in dB(A) | 71 |

| | |
|--------------------------------------|----|
| Sound power level guaranteed (Lwa) | 87 |
| Acoustic pressure level @7m in dB(A) | 58 |

APM303, comprehensive and simple



The APM303 is a versatile unit which can be operated in manual or automatic mode. It offers the following features:

Measurements:
 phase-to-neutral and phase-to-phase voltages, fuel level
 (In option : active power currents, effective power, power factors, Kw/h energy meter, oil pressure and coolant temperature levels)

Supervision:
 Modbus RTU communication on RS485

Reports:
 (In option : 2 configurable reports)

Safety features:
 Overspeed, oil pressure, coolant temperatures, minimum and maximum voltage, minimum and maximum frequency (Maximum active power P<66kVA)

Traceability:
 Stack of 12 stored events

For further information, please refer to the data sheet for the APM303.

TELYS, ergonomic and user-friendly



The highly versatile TELYS control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The TELYS offers the following functions:

Electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

Ergonomics: wheel for navigating around the various menus.

Communication: remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.

M80, transfer of information




The M80 is a dual-function control unit. It can be used as a basic terminal block for connecting a control box and as an instrument panel with a direct read facility, with displays giving a global view of your generating set's basic parameters.

Offers the following functions:

Engine parameters: tachometer, working hours counter, coolant temperature indicator, oil pressure indicator, emergency stop button, customer connection terminal block, CE.

APM403, basic generating set and power plant control



The APM403 is a versatile control unit which allows operation in manual or automatic mode

Measurements : voltage and current

kW/kWh/kVA power meters

Standard specifications: Voltmeter, Frequency meter.

Optional : Battery ammeter.

J1939 CAN ECU engine control

Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.

Engine parameters: Fuel level, hour counter, battery voltage.

Optional (standard at 24V): Oil pressure, water temperature.

Event log/ Management of the last 300 genset events.

Mains and genset protection

Clock management

USB connections, USB Host and PC,

Communications : RS485 INTERFACE

ModBUS protocol /SNMP

Optional : Ethernet, GPRS, remote control, 3G, 4G,

Websupervisor, SMS, E-mails